UniFi Al LPR Datasheet

UniFi - Al LPR SKU: UB-UVC-AI-LPR



The Ubiquiti UVC AI LPR is a high-performance 4K bullet IP camera designed for precise license plate recognition (LPR). With 3x optical zoom and long-range IR night vision, it captures clear 8MP video and recognizes license plates on vehicles moving up to 90 km/h. Its rugged, weatherproof design ensures reliable outdoor performance, and it supports dual-lane coverage for comprehensive traffic monitoring1. Ideal for high-traffic areas, this camera delivers exceptional LPR results in all lighting conditions



UniFi Al LPR Datasheet

UniFi - Al LPR SKU: UB-UVC-AI-LPR

Mechanical	
Dimensions	130 x 151.4 x 302.9 mm
	(5.1 x 6 x 11.9")
IR Night Vision	15 m (50 ft)
Optical Zoom	3x
License Plate Recognition	Yes
Smart Detections (People, Vehicles, Animals) Yes	
Resolution	4K
Field of View	Wide: H 109.9°, V 60°, D 127.7°
	Tele: H 35°, V 19.8°, D 40°
Audio	Microphone
Weatherproofing	IP66
Tamper Resistance	IK04
Mounting	Wall, Ceiling, Pole mount (Included)
	Junction Box, Angled Base (Optional)
UniFi Application Suite	Protect
Performance	
Networking Interface	GbE RJ45 port
Video	
Image Settings	Color, brightness, sharpness, contrast, white balance,
	exposure control, 2DNR, 3DNR, NR by motion, masking,
	text overlay
Max. Frame Rate	30 FPS
Resolution	8MP 3840 x 2160 (16:9)
Optics	
Sensor	1/1.8" 8MP
Lens	F 4.1–12.3 mm; $f/1.53-f/3.3$
IR Capture Distance	15 m (50 ft)
LPR Night Mode	LPR optimization filter

UniFiAl LPR
Datasheet

UniFi - Al LPR SKU: UB-UVC-AI-LPR

Hardware

Max. Power Consumption Supported Voltage Range **Power Method** Processor Pole Mount Diameter Weight **Enclosure Material** Mount Material Button **Ambient Operating Temperature Ambient Operating Humidity** Certifications Cable Cable Connector Type **Cable Diameter** Cable Lengt Jacket Material Jacket Enclosure Dimensions Jacket Enclosure Material **Expansion Slot**

25.5W 42.5–57V DC PoE+ Quad-core Arm® Cortex®-A53 based chip 38–50 mm (1.5–2") 1.5 kg (3.3 lb) Aluminum alloy, polycarbonate Aluminum Alloy Factory Reset -20 to 50° C (-4 to 122° F) 10 to 90% noncondensing FCC, IC, CE

RJ45 4.5 mm (0.2") 30 cm (1 ft) Thermoplastic elastomer Ø20 x 70.6 mm (0.8 x 2.8") Thermoplastic elastomer, polycarbonate, silicone rubber Micro SD memory card



UniFi Al LPR Datasheet

UniFi - Al LPR SKU: UB-UVC-AI-LPR



*The AI-LPR is optimized to exclusively capture reflective or non-reflective license plates at night. Install additional cameras to capture other vehicle details.



